

N0014L Process Geometry

Features

- Low Input Capacitance: 2.3pF Typical
- Low Gate Leakage: 2.0pA Typical
- High Breakdown Voltage: -30V Typical
- High Input Impedance
- Small Die: 365um X 365um X 203um
- Bond Pads: 90um X 90um and 66um Dia.
- Substrate Connected to Gate
- Au Back Side Finish


Applications

- Small Signal Amplifiers
- Audio Amplifiers
- Low Noise High Gain Amplifier
- RF Amplifiers
- Custom Part Options

Description

The InterFET N0014L Geometry is targeted for low noise high gain amplifier applications. The low input capacitance makes it ideal for higher frequency applications.

Geometry Top View



Standard Parts

- IF140, IF140A

Product Summary

Parameters	Min	Typ	Max	Unit
BV _{GSS} Gate to Source Breakdown Voltage	-15	-30		V
I _{DSS} Drain to Source Saturation Current	0.5	10	20	mA
V _{GS(off)} Gate to Source Cutoff Voltage	-0.5		-7	V
G _{FS} Forward Transconductance		4.0		mS

Maximum Ratings (@ T_A = 25°C, Unless otherwise specified)

Parameters	Min	Typ	Max	Unit
V _{RGS} Reverse Gate to Source or Drain Voltage	-15	-30		V
I _{FG} Continuous Forward Gate Current			10	mA
T _J Operating Junction Temperature	-55		150	°C
T _{STG} Storage Temperature	-65		175	°C



Disclaimer: It is the Buyers responsibility for designing, validating and testing the end application under all field use cases and extreme use conditions. Guaranteeing the application meets required standards, regulatory compliance, and all safety and security requirements is the responsibility of the Buyer. These resources are subject to change without notice.

Electrical Characteristics


Static Characteristics (@ TA = 25°C, Unless otherwise specified)

Parameters	Conditions	Min	Typ	Max	Unit
BV _{GSS} Gate to Source Breakdown Voltage	I _G = -1μA, V _{DS} = 0V	-15	-30		V
I _{GSS} Gate to Source Reverse Current	V _{GS} = -10V, V _{DS} = 0V		-2	-100	pA
V _{GS(OFF)} Gate to Source Cutoff Voltage	V _{DS} = 10V, I _D = 1nA	-0.5		-7	V
I _{DSS} Drain to Source Saturation Current	V _{DS} = 10V, V _{GS} = 0V	0.5	10	20	mA


Dynamic Characteristics (@ TA = 25°C, Unless otherwise specified)

Parameters	Conditions	Min	Typ	Max	Unit
G _{FS} Forward Transconductance	V _{DS} = 10V, V _{GS} = 0V, f = 1kHz		4.0		mS
C _{iss} Input Capacitance	V _{DS} = 15V, V _{GS} = 0V, f = 1MHz		2.3		pF
C _{rss} Reverse Transfer Capacitance	V _{DS} = 15V, V _{GS} = 0V, f = 1MHz		0.5		pF
e _n Noise Voltage	V _{DS} = 10V, I _D = 0.5mA f = 1kHz		4		nV/√Hz

Typical N0014L Characteristics




Typical N0014L Characteristics (Continued)



N0014L Die Geometry Mechanical

Raw Die Dimensions



1. All linear dimensions are in micrometers.